

## PROCESS BASE OIL GRADE 150

Grade 150 is defined as a light grade process base oil at the lower end of the specifications for Grade I light base oils. They are mainly used in lubricant and lubricant additives production. It is a Group I base oil (mineral based non-synthetic base oil) which is derived from re-refining used or lubricants contaminated with particulate matter and other soluble materials.

### Appearance

Bright & Clear

### CAS NUMBER

64741-89-5

### Quality Data

Parameter	Method	Unit	Typical Result
Color	ASTM D1500	-	MAX 3
Density @ 15°C	ASTM D1298	Kg/L	0.880
Viscosity @ 40°C	ASTM D445	cSt	25
Viscosity @ 100°C	ASTM D445	cSt	4.5
Viscosity Index	ASTM D2270	-	Min 80
Flash Point	ASTM D93	°C	160
Pour Point	ASTM D97	°C	> - 6
Water Content	ASTM D95	% Vol	< 0.05
Ash Content	ASTM D482	% (m/m)	< 0.01
Sulphur Content	ASTM D4294	% (m/m)	< 0.1

***For Health & Safety information refer to the most current version of the product MSDS***

The data contained herein is believed to be accurate at the time of distribution. However, **Techinergy** does not assume any legal liability whatsoever for the accuracy or completeness of the information contained herein. Users should undertake sufficient verification and testing to determine the suitability of this product for their own purposes.