



BASE OIL N 150 (GRP II)

It is defined as a light grade base oil at the lower end of the specifications for Grade I light base oils. They are mainly used in lubricant and lubricant additives production. It is a Group I base oil which has undergone solvent refining and dewaxing processes. To finish the refining it was hydrogen treated to clear out any impurities.

Appearance		CAS NUMBER	
Light Color High Viscous		64741-89-5	
Quality Data			
Parameter	Method	Unit	Typical Result
Color	ASTM D1500	-	0.5
Density @ 15°C	ASTM D1298	Kg/L	0.859
Viscosity @ 40°C	ASTM D445	cSt	31.2
Viscosity @ 100°C	ASTM D445	cSt	5.43
Viscosity Index	ASTM D2270	-	110
Flash Point	ASTM D93	°C	220
Pour Point	ASTM D97	°C	-15
Water Content	ASTM D95	% Vol	<0.02
Ash Content	ASTM D482	% (m/m)	<0.01
Sulphur Content	ASTM D4294	% (m/m)	<0.1

For Health & Safety information refer to the most current version of the product MSDS

The data contained herein is believed to be accurate at the time of distribution. However, **Techinergy** does not assume any legal liability whatsoever for the accuracy or completeness of the information contained herein. Users should undertake sufficient verification and testing to determine the suitability of this product for their own purposes.