

BASE OIL SN 150

Base oils are used to manufacture products including lubricating greases, motor oil and metal processing fluids. Base oil is typically defined as oil with a boiling point range between 550 and 105° F, consisting of hydrocarbons with 18 to 40 carbon atoms. This oil can be either paraffinic or naphthenic in nature depending on the chemical structure of the molecules.

Appearance	CAS NUMBER
Visual Bright & Clear	64742-65-0

Quality Data

Parameter	Method	Unit	Typical Result
Color	ASTM D1500	-	1.5
Density @ 15°C	ASTM D1298	Kg/L	0.873
Viscosity @ 40°C	ASTM D445	cSt	21
Viscosity @ 100°C	ASTM D445	cSt	4.5
Viscosity Index	ASTM D2270	-	107
Flash Point	ASTM D93	°C	210
Pour Point	ASTM D97	°C	- 3
Water Content	ASTM D95	% Vol	Max 0.05
Ash Content	ASTM D482	% (m/m)	0.01
Sulphur Content	ASTM D4294	% (m/m)	0.5

For Health & Safety information refer to the most current version of the product MSDS

The data contained herein is believed to be accurate at the time of distribution. However, **Techinergy** does not assume any legal liability whatsoever for the accuracy or completeness of the information contained herein. Users should undertake sufficient verification and testing to determine the suitability of this product for their own purposes.