

## Bitumen 60/70

Cut Back Bitumen is an oil based substance. It is a semi-solid hydrocarbon product produced by removing the lighter fractions (such as liquid petroleum, gas, petrol & diesel) from heavy crude oil during the refining process.

### Appearance

A Semi-solid, Brown to Black Material

### CAS NUMBER

8052-42-4

### Quality Data

Parameter	Method	Unit	Typical Result
Color	ASTM D1500	-	Black
Density	ASTM D70	Kg/m <sup>3</sup>	1.010 - 1.060
Flash Point	ASTM D92	°C	> 225
Penetration @ 25°C	ASTM D5	°C	60/70
Softening Point	ASTM D36	°C	49/56
Deuctility @ 25°C	ASTM D113	Cm/s	> 100
Loss of Heating	ASTM D6	Wt %	0.5 Max
Drop in penetration after heating	ASTM D6 & D5	Wt %	20 Max
Retained Penetration	ASTM D5	Wt %	> 50
Bitumen Content	ASTM D4	Wt %	> 99.5
Solubility in sc2	ASTM D4	Wt %	> 99.5 Min
Spot Test	A.A.S.H.O.T.102	-	Negative

***For Health & Safety information refer to the most current version of the product MSDS***

The data contained herein is believed to be accurate at the time of distribution. However, **Techinergy** does not assume any legal liability whatsoever for the accuracy or completeness of the information contained herein. Users should undertake sufficient verification and testing to determine the suitability of this product for their own purposes.