

Lubisle® 4T Semi-Synthetic SAE 15W-50

High-Performance Semi-Synthetic Motorcycle Engine Oil

Customer Benefits

- **Enhanced Engine Protection:** Offers superior wear protection for critical engine components, ensuring extended engine life.
- **Excellent High-Temperature Stability:** Maintains performance under high-stress and high-temperature conditions.
- **Smooth Clutch Performance:** Formulated to provide smooth and reliable clutch engagement, improving overall riding experience.
- **Sludge and Deposit Control:** Keeps the engine cleaner by preventing the formation of harmful deposits and sludge.
- **Improved Fuel Efficiency:** Reduces internal friction, leading to better fuel economy.
- **Extended Drain Intervals:** Designed for longer oil change intervals, reducing maintenance frequency.

Applications

Lubisle 4T Semi-Synthetic SAE 15W-50 is ideal for use in 4-stroke motorcycles, including sport bikes, cruisers, and touring bikes. It is recommended for engines requiring **API SL**, **JASO MA2** lubricants, and is compatible with both air-cooled and liquid-cooled engines.

Typical Key Properties

Property	Test Method	Value
SAE Grade	-	15W-50
Product Code	-	TL15W50
Density at 15°C (kg/l)	ASTM D4052	0.865
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	129
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	17.5
Viscosity Index	ASTM D2270	150
Pour Point (°C)	ASTM D5950	-30
Flash Point (°C)	ASTM D92	230
Phosphorus (mass %)	ASTM D4951	0.085
Zinc (mass %)	ASTM D4951	0.095

Disclaimer: Minor variations in product typical test data are to be expected in normal manufacturing.

Performance Standards

- **API SL**
- **JASO MA2**