

Lubisile® Fully Synthetic Hybrid SAE 0W-20

Passenger Car Motor Oil

Customer Benefits

- **Excellent Hybrid Engine Protection:** Ensures long-lasting protection for hybrid engines, enhancing their lifespan.
- **Maintains Optimal Hybrid Power and Performance:** Smoother oil flow helps maintain peak hybrid performance.
- **Specifically Formulated for Hybrids:** Tailored to meet the unique requirements of hybrid vehicles.
- **Reduces Fuel Consumption:** Enhances fuel efficiency for better mileage.
- **Extended Drain Intervals:** Longer intervals between oil changes, saving time and maintenance costs.
- **Low Oil Consumption:** Helps reduce the frequency of top-ups.

Applications

Lubisile Fully Synthetic Hybrid SAE 0W-20 is ideal for use in hybrid and gasoline vehicles that require an **API SP** or **ILSAC GF-6A** SAE 0W-20 lubricant.

Typical Key Properties

Property	Test Method	Value
SAE Grade	-	0W-20
Product Code	-	TL0W20
Density at 15°C (kg/l)	ASTM D4052	0.8472
Kinematic Viscosity @ 40°C (mm ² /s)	ASTM D445	43.5
Kinematic Viscosity @ 100°C (mm ² /s)	ASTM D445	8.4
Viscosity Index	ASTM D2270	172
Pour Point (°C)	ASTM D5950	-45
Flash Point (°C)	ASTM D92	242
Phosphorus (mass %)	ASTM D4951	0.066
Ash, Sulphated (mass %)	ASTM D874	0.77
Zinc (mass %)	ASTM D4951	0.076

Disclaimer: Minor variations in product typical test data are to be expected in normal manufacturing.

Performance Standards

- **API SP/Resource Conserving**
- **ILSAC GF-6A**